



Engineered with a durable **All-weather Environmental Feature-Set**, SunBriteTV televisions are designed for permanent outdoor installation:

- The extra bright 46-inch full-HD 1080p LCD screen is integrated into an all-weather exterior that protects the internal components from rain, dirt, insects and scratches.
- **Multi-fan Airflow System** keeps the unit cool and dry in temperatures up to 122 degrees F.
- **Internal Thermostatically-Controlled Heater** protects TV in temperatures as low as -24 degrees F.
- **Innovative Water-tight Cable Entry System** with pass-through design keeps cables dry and allows for easy hook-ups.
- **Anti-Reflective Window** reduces glare, increases contrast and protects the LCD screen.

Model 4630HD


Model 4630HD is a bright 46" full-HD 1080p LCD all-weather outdoor television.

Specifications

LCD Screen	46-inch diagonal TFT Active Matrix
Resolution	1920 x 1080 full-HD 1080p
Aspect Ratio	16:9
Contrast Ratio	4000:1
Viewing Angle	176° x 176°
Response Time	8.0 milliseconds
TV formats	1080p, 1080i, 720p, 480p, 480i
Input Connectors:	
RF	Antenna/CATV (ATSC/QAM/NTSC) x1
HDMI	HDMI™ Input x4
Video Composite	S-Video x1 and Composite Video x1, L/R Audio Inputs x1
Video Component	YPbPr plus Stereo Audio x2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	Discrete IR Control, Concealed IR Window, RS232 Optional
Audio Out	TosLink Digital Optical x1
Speakers	20-watt Built-in Speakers
Exterior	Outdoor rated ASA plastic resin
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max
Operating Temp.	-24° to 122° F. (-31° to 50° C.) *
Non-op. Temp. (Off-mode with power applied)	-24° to 140° F. (-31° to 60° C.) The non-operating temperature feature requires power to be applied
Accessories Included	Water-resistant remote control
TV Dimensions	45.51" W x 29.13" H x 6.68" D
Shipping Dimensions	52" W x 42" H x 13" D
Weight	80.0 lbs.
Shipping Weight	127.0 lbs.
Warranty	One-year, in-factory, parts and labor

The **Control Feature-Set** maximizes system integration and programming security:

- **IR input control**
- **Remote Control Lock-out** prevents unauthorized users from changing the programming.
- **Sleep Mode** automatically turns the TV to the Off mode when the signal is removed, and turns it back to On when the signal is restored.



All measurements are in inches

Optional Accessories

SB-WM46	Articulating wall mount with tilt and swivel, arm and pan. Dual arm articulation extends to 21". Customized to fit--includes stainless steel and/or zinc-plated hardware.
SB-WM46NA	Wall mount with tilt--non articulating. Customized to fit--includes stainless steel and/or zinc-plated hardware.
SB-CM46A12	Ceiling mount with tilt. Includes adjustable extension column provides up to 6" above unit to ceiling in <u>above unit</u> to ceiling in 1" increments without disassembly, and speed connect ceiling plate. Meets VESA standards.
SB-DP46XA	Deck/Planter pole (Requires purchase of wall mount SB-WM46 or SB-WM46NA). Special order item.
SB-FMT32	RadioFM™ transmits audio from TV to FM radio
SB-TS46	Removable table top stand. TV with table top stand is 30.58" H x 11.70"D); 9.5 lbs.
SB-DC461	Outdoor TV dust cover

*Temperature range is for operation in shaded location.

Specifications may be subject to change.

Patent pending. All rights reserved. (C) 2011 SunBriteTV® LLC Rev. 4630HD -1103